



Chemical system:

Alkaline, MnO₂ / KOH / Zn

Designations:

LR43, AG12, 301, SR43

Nominal Voltage:

1.5 V

Nominal Capacity:

100 mAh at 6.8 kOhms to 0.9 Volts

Weight:

1.48 g

Volume:

0.42cm³

Recommended storage temperature:

10 – 25 °C, RH no more than 75%.

Operating temperatures:

-10 – 45 °C

Reaction:

2MnO₂ + Zn + H₂O → 2MnOOH + ZnO

Terminals:

Flat contacts

Jacket:

None

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2013/56/EU & 2006/122/EC.
- 6) SDS sheets are available on request from Strand Europe Ltd.

DANGER: Keep batteries out of reach of children. If swallowed, the battery can cause serious injury or death. Severe burns can occur within hours of ingestion. If you suspect that a battery has been ingested, seek immediate medical attention. Have doctor call CHEMTREC Day or Night on 1-800-424-9300 / +1 703-527-3887. **CAUTION:** Ensure that the battery compartment is completely secure, meaning closed and locked to prevent easy access by children. If the battery compartment cannot be completely secured, discontinue use of the product, or keep out of sight and reach of children.



Brand Licensee

KODAK Batteries
KODAK LED Bulbs
KODAK Headphones
KODAK LED Flashlights

The Kodak trademark, logo and trade dress are used under license from Kodak.
© 2021 STRAND EUROPE LTD.
www.kodakbatteries.strandeuroltd.com

Page 1 of 1

Version: 2.2

Date: 19 January 2021