KODAK Products

Product Data Sheet


D-01-232-10

KODAK MAX SUPER Alkaline Battery

Effective: 19/01/2021







Dimensions are in millimetres

Chemical system: Alkaline, MnO2 / KOH / Zn

Designations: LR626, AG4, 377, SR66

Nominal Voltage: 1.5 V

Nominal Capacity: 18 mAh at 22 kOhms to 0.9 Volts

Weight: 0.28 g **Volume:** 0.09cm³

Recommended storage temperature: 10 - 25 °C, RH no more than 75%.

Operating temperatures: $-10 - 45 \, ^{\circ}\text{C}$

Reaction: $2MnO_2 + Zn + H_2O \rightarrow 2MnOOH + ZnO$

Terminals: Flat contacts

Jacket: None

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2013/56/EU & 2006/122/EC.
- 6) SDS sheets are available on request from Strand Europe Ltd.

DANGER: Keep batteries out of reach of children. If swallowed, the battery can cause serious injury or death. Severe burns can occur within hours of ingestion. If you suspect that a battery has been ingested, seek immediate medical attention. Have doctor call CHEMTREC Day or Night on 1-800-424-9300 / +1 703-527-3887. **CAUTION:** Ensure that the battery compartment is completely secure, meaning closed and locked to prevent easy access by children. If the battery compartment cannot be completely secured, discontinue use of the product, or keep out of sight and reach of children.

