

**Product Data Sheet** 

D-00-L25

## **KODAK LED Flashlight Lantern 120**

Effective: 31/11/2017





Designation	KODAK LED Flashlight Lantern 120
Dimensions	L 105 mm x W Ø 60 mm
Weight	68.5 g ± 5 %(without battery)
Battery size Application	3 x AAA
Battery type	Ni-MH, Alkaline, Zinc-Chloride, Lithium AAA.
Operating Modes	1 <sup>st</sup> press to the on/off button- High output narrow beam. 2 <sup>nd</sup> press to the on/off button-6 SMD LED's high broad beam. 3 <sup>rd</sup> press to the on/off button-6 SMD LED's low broad beam 4 <sup>th</sup> press to the on/off button-6 SMD LED's flashing output.
Features	Carabiner
LED Light	120 lumens
Weather Resisting Rating	IP64 (dust-tight, protected against water sprayed from all directions ).
Compliance	RoHS Directive 2002/95/EC, EU WEEE Directive 2012/19/EU and also compliant with EU REACH requirements
Housing material	ABS
Operating temperature	-10°C- 60°C ; 45-85% RH

\* Denotes Colour options.

The Data in this publication represents product tested under the conditions specified. They do not represent standards or specifications which must be met. Strand reserves the right to change and improve product characteristics at any time. Contents herein do not constitute a warranty.



The Kodak trademark and the Kodak trade dress are used under license from Kodak. © 2017 STRAND EUROPE LTD www.kodakbatteries.strandeurope.com

Page **1** of **1** Version: 1.0 Date: 17 March 2016